

MSA 6'8" X 12' LOW PROFILE HEAVY DUTY DUMP TRAILER

HEAVY DUTY DUMP TRAILER



Slide-out ramps store easily on lower frame. Taillights are positioned on the sides to prevent damage when dumping.

VERSATILITY AND VALUE IN A MULTI-PURPOSE TRAILER

This multi-purpose, heavy-duty trailer serves as both a dump trailer and a transport, providing more versatility and value for your investment than most trailers on the market. Use it to transport wood, landscaping materials, tractors, mowers, ATVs and more. The multi-purpose bi-fold gate opens as a traditional tailgate or barn-door style, or you can use its spreader option for activities such as spreading dirt or fertilizer. Slide-out ramps further expand the trailer's versatility as a transport. All hinge and pivot points are constructed of 1" thick material and are greasable.

This low-profile trailer features a sturdy, full tube-frame mild steel construction, one-piece floor and sides, high-flow Monarch hydraulics with telescoping cylinders, and 5200 lb. Dexter axles. This trailer will handle your toughest loads with ease!



GENERAL WELDING & FABRICATING, INC.

991 MAPLE ROAD • ELMA, NY 14059 • 716-652-0033

TOLL FREE: 866-WNY-BOSS • www.gwfab.com

STANDARD MULTI-FUNCTION GATE DOES IT ALL!



Bi-fold gate allows for dumping large piles.



Rear doors double as spreader gate.



Slide-out ramps expand versatility.

SPECIFICATIONS

MODEL #68X12LPD

Dump Box – 12' long x 6'8" wide

Full Tubing Frame – mild steel construction

Cross Members – 2 x 3 x 1/8" tubing on 12" centers

10-Gauge, One-Piece Floor

11-Gauge, One-Piece Sides – 24" high

Hinge/Pivot Points – constructed of 1" thick material, greasable

(2) 18" x 60" Slide Out Ramps

Multi-Purpose Bi-fold Gate – includes barn door and spreading option

High Flow Monarch Hydraulics – standard 10-ft. remote cord

Adjustable Needle Valve – for down speed control

Hydraulic Lines – loomed to prevent chafing

Dual 3.0 x 2.0 x 48.0 Telescopic Cylinders

Standard (2) 5200 lb. Dexter Axles with E-Z Lube

12-1/4" Electric Brakes

15" 6-bolt White-spoked Wheels

ST225-75 D-15 Tires

Rear Lights – rubber mounted and positioned on the side to avoid damage

Jacketed Wiring

Plastic Tool/Pump Compartment

Under Body Storage Compartment

7000 lb. Jack

Adjustable Pintle or Ball Coupler

Spare Tire Mount Provisions

(6) D-Rings – mounted to floor

3900 lbs. Overall Weight



Plastic compartment holds controls, hydraulic pump and battery.*

OPTIONS:

6000 lb. Axles**, 7200 lb. Axles**, 6 ft. Ramps, Dual Battery, Wireless Control, Tarp, LED Lights, Goose-Neck Tongue, Coal Chute, Electric Jack, Radial or Bias Tires

*Note: 12V deep-cycle battery not included.

**Note: 6000 lb. or 7200 lb. axles require 16" wheels and tires

We Can
Design or Build
Anything

